



Pro-Gro Mixes & Materials Dave Andrews PO Box 1127 Tualatin, OR 97062

Date Received Jan-28-2020 Date Reported Feb-3-2020 Facility Product Development

Maximum Media Density for Dead Load Analysis of Green Roof Systems [‡]

]		Water Permeability (Saturated Hydraulic Conductivity)		Initial Media Density (Application Density)		Maximum Media Density (Saturated Density)		Maximum Media Water	Air-filled Porosity ^{‡‡}	Dry Media Density	
Lab ID#	Sample Name	(in/hr)	(mm/min)	(lb/ft ³)	(g/cm ³)	(lb/ft ³)	(g/cm ³)	Retention (%)	(%)	(lb/ft ³)	(g/cm ³)
20010059-4	Landscape Blend #2	3.9	1.6	66.4	1.06	89.8	1.44	59	7	52.8	0.85
				-					-		

		Initial Sample Wt.	Sample Volume	Initial Sample Height	Final Sample Height	Sample Wt. After Draining	Total Pore Space	pH ^{‡‡‡}	Electrical Conductivity	Organic Matter**	Organic Matter**
Lab ID#	Sample Name	(Kg)	(m³)	(cm)	(cm)	(Kg)	(%)		mmhos/cm	(%)	g/L
20010059-4	Landscape Blend #2	2.017	0.0019	10.4	10.7	2.7	66	6.6	0.2	14.1	119.8

Particle Size Evaluation*

						% Passing US sieve (mm)						
Lab ID#	Sample Name	% Sand	% Silt	% Clay	Gravel	Gravel	Gravel	V. Coarse	Medium	V. Fine		
		2.0 - 0.063 mm	0.063-0.002 mm	< 0.002mm	3/8"	1/8" (3.17)	10 (2.0)	18 (1.0)	60 (0.25)	230 (0.063)		
20010059-4	Landscape Blend #2	63.9	15.8	6.3	99.5	87.6	86.1	81.3	47.5	22.1		

^{‡‡}At Maximum Media Density (Water-holding Capacity)

****ASTM D4972 w CaCl₂ (not screened)

*ASTM F1632 Method B

**Ashed at 550° C (FLL Guidelines) Electrial Conductivity (1:5)

Samples were tested as received and comments pertain only to the samples shown.

This report may not be reproduced in part, but only in full.

Sample condition upon receipt was normal.

[‡] ASTM E2399

Samples were received with a transmittal letter.

Reviewed by _____

Page 1 of 1